

PRODUCT DESCRIPTION

CanLine AD-PETRO HXL Oil delivers the latest development in lubricating-oil technology to maximize the protection for the newest engine fueled by gasoline, diesel, LPG/CNG and operating under severest conditions.

By meeting the highest API performance level SL, CanLine AD-PETRO HXL oil exceeds most demanding requirements in relation to engine emission control, oil consumption and volatility etc.

APPLICATIONS / BENEFITS

- ✓ Formulated for stop and go driving.
- ✓ Silk smooth operation of all high performance engines.
- ✓ Meets the highest standards for gasoline and LPG/CNG engines.
- ✓ Protects engines under severe driving conditions.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS	
SAE Viscosity Grade		15W40	20W50
Specific Gravity @ 15°C	ASTM D-4052	0.885	0.893
Flash Point, °C	ASTM D-92	228	232
Pour Point, °C	ASTM D-97	-27	-18
Kinematics Viscosity			
@ 40°C (cSt)	ASTM D-445	106.4	192.2
@ 100°C (cSt)	ASTM D-445	14.5	20.50
Viscosity Index	ASTM D-2270	140	124
TBN (mgKOH/g)	ASTM D-2896	8.9	8.9

The values mentioned are typical, depending upon the quality of the base oil available and cannot be used to reject the product. However, these properties can be altered to meet the specific requirement of the process/equipment.

PERFORMANCE STANDARDS

- API SL/CF
- ACEA A2-96#, A3-98,B2-98,B3-98,E2-96#2