



CanLine Heat Transfer Oil

PRODUCT DESCRIPTION

CanLine Heat Transfer Oil is a premium Heat Transfer Oil designed to give outstanding service in a variety of applications. It is blended from high viscosity index paraffinic base oils and fortified with oxidation inhibitors to enhance high temperature performance and stability. **CanLine Heat Transfer Oil** is resistant to oxidation and high temperature degradation, giving this fluid a long usable life and minimizing deposit formation.

APPLICATIONS / BENEFITS

- ✓ Good Thermal Stability
- ✓ Blended with naturally high VI base oils.
- ✓ Contains high temperature oxidation inhibitors.
- ✓ Minimizes deposit formation.
- ✓ Long fluid life.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
ISO Viscosity Grade		22	46	68	150
Specific Gravity @ 15 ⁰	ASTM D-4052	0.862	0.879	0.884	0.891
Flash Point, ⁰ C	ASTM D-92	194	226	236	254
Pour Point, ⁰ C	ASTM D-97	- 18	- 15	- 15	-9
Kinematics Viscosity @ 40 ⁰ C (cSt)	ASTM D-445	23	46	65	140
@ 100 ⁰ C (cSt)	ASTM D-445	4.5	6.6	8.3	14.1
Viscosity Index	ASTM D-2270	103	100	99	98

The values mentioned are typical, depending upon the quality of the base oil available and cannot be used to reject the product. However, these properties can be altered to meet the specific requirement of the process/equipment.
