



## CanLine ULTRA-PETRO HXJ Oil

---

### PRODUCT DESCRIPTION

CanLine ULTRA-PETRO HXJ oil is formulated with the most advanced additive components for its class, protecting engines from the stress of cold starts as well as short trip driving. It provides high temperature protection in all grades, exceeding the toughest standards against thermal breakdown.

### APPLICATIONS / BENEFITS

- ✓ Formulated for stop and go driving.
- ✓ Protects against rust and corrosion.
- ✓ Meets the highest standards for automotive engine wear protection.
- ✓ Protects engines under severe driving conditions.
- ✓ Eliminates the need for extra oil additives.
- ✓ Meets the highest standards for gasoline and LPG/CNG engines

### TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS	
SAE Viscosity Grade		15W40	20W50
Specific Gravity @ 15°C	ASTM D-4052	0.886	0.892
Flash Point, °C	ASTM D-92	230	238
Pour Point, °C	ASTM D-97	-27	-18
Kinematics Viscosity			
@ 40°C (cSt)	ASTM D-445	110	175
@ 100°C (cSt)	ASTM D-445	14.6	18.78
Viscosity Index	ASTM D-2270	145	121
TBN (mgKOH/g)	ASTM D-2896	9	9

The values mentioned are typical, depending upon the quality of the base oil available and cannot be used to reject the product. However, these properties can be altered to meet the specific requirement of the process/equipment.

### PERFORMANCE STANDARDS

- API SJ/CF
-